

SPECIFICATIONS

All-in-One Video Conferencing Solution for Unparalleled Collaborations



reddot award 2019
best of the best

*D7 in this image is not in 1:1 ratio



PRODUCT	D7 55" Dual		
SOFTWARE	DTEN D7 OS, provisioned by D7 OS		
ALL-IN-ONE D7	LED 55" Multi-Touch Display x 2 4K Camera 16-Microphone Array Integrated Speakers		
DISPLAY	LED 55" x 2, 4K, 16:9 Capacitive Touch Screen		
CAMERA SYSTEM	Fixed Lens, Infinite Focus F-value: 2.8 4K Diagonal Field of View (FOV): 86 Degrees Unit Mounted Tilt: 15 Degrees		
AUDIO SYSTEM	16 Elements Microphone Array Integrated 2-Channel Stereo Speakers High Quality 20-kHz Audio Zoom Rooms Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction		
NETWORK	Ethernet (RJ-45) 100/1000 Mbps Wi-Fi 802.11a/b/g/n, 802.11ac (2.4 and 5 GHz) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support		
INPUTS AND OUTPUTS		HDMI Out x 1 USB 3.0 x 1 3.5-mm Audio Jack x 1 Microphone x 1 Ethernet LAN (RJ45) x 1	
POWER		Auto-Sensing Power Supply 100 to 240 VAC, 50 to 60 Hz	
VESA		400 x 300 mm	
PRODUCT DIMENSIONS (Each Unit)		49 x 30.5 x 2.13 in (124.49 x 77.38 x 5.42 cm)	
PRODUCT WEIGHT (Each Unit)		50.7 lb (23 kg)	
PACKAGE DIMENSIONS (Single Package)		56 x 36 x 8.5 in (142 x 92 x 21.5 cm)	
PACKAGE WEIGHT (Single Package)		77 lb (35 kg)	
OPERATING TEMPERATURE AND HUMIDITY		Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH	
LANGUAGE SUPPORT		English * Additional languages to be supported in future software release	
SYSTEM REQUIREMENT		Zoom Rooms License	
APPROVALS AND COMPLIANCE		FCC, CE, CCC, ROHS, ACMA, CB PSE, TELEC, BIS	

*Specifications are subject to change without prior notice.

Zoom Rooms Simplified • Affordable