Tabletop Conference Device for Crestron Home™ OS



- Tabletop conference device for Crestron Home™ OS
- Simple, familiar UI consistent with mobile devices and touch screens running the Crestron Home app
- Convenient in-call volume control
- Seamless audio conferencing from a connected computer
- Sonos® app integration
- Dynamic, low-profile form factor suitable for any home office environment
- Simple installation no custom design, programming, or software installation required
- Power over Ethernet+
- Ethernet or dual-band Wi-Fi® communications
- Robust network security

The Crestron® UC-MM30-R tabletop conference device pairs an enterprise-grade speakerphone with the powerful control of the Crestron Home operating system to provide one convenient home office companion.

Native Crestron Home™ OS Experience

The tabletop conference device natively runs the Crestron Home app and offers complete integration with an existing Crestron Home system to provide lighting, shade, climate, media, security, and camera control. The Crestron Home app also offers the ability to create and recall scenes to achieve a desired ambiance throughout a home. The intuitive user interface allows for dynamic home control and convenient in-call volume control via the device's large 7 in. HD color touch screen.

Seamless Audio Conferencing

Simply connect the included USB cable from the conference device to a computer for a seamless audio conferencing experience. When connected, the conference device acts as an AEC-enabled USB speakerphone with four built-in omnidirectional microphones for 360° audio pickup.

Whole-House Music Control with the Sonos App

Sonos and Crestron have partnered to provide a powerful whole-house music experience. From the conference device, browse for tracks, artists, or playlists using all the services available from Sonos and instantly play them in any room using Sonos® wireless speakers or a Crestron Sonnex® multiroom audio system. The Sonos app runs natively on the conference device, enabling enhanced control of Sonos products as part of a complete Crestron system. The app checks for updates nightly so it's always current, and support for the Sonos S2 App is provided.

Perfect for the Home Office

The sleek, low-profile form factor of the conference device is suitable for any home office environment. The minimal amount of device connections eliminates cable clutter for a clean user experience and simple installation.

Versatile Networking Options

An Ethernet LAN connection is the only wiring requirement for the included conference device, containing all control and power signals within a single wire. For maximum convenience, the device can also connect securely to the network via Wi-Fi communications.

Power Over Ethernet+

Using PoE+ technology, the conference device is powered directly through the network cable. With PoE+, the need for a local power supply or dedicated power wiring is eliminated, though a PoE+ injector is also included to accommodate for installations that do not support PoE+.

Robust Network Security

The tabletop conference device employs secure networking with features such as 802.1X authentication, TLS encryption, and Active Directory® service integration.



Tabletop Conference Device for Crestron Home™ OS

Specifications

Communications

Ethernet 10/100 Mbps, auto-switching,

> auto-negotiating, auto-discovery, full/half duplex, DHCP, TCP/IP, UDP/IP, CIP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), SRTP, IEEE 802.1X, Active Directory® authentication, digest access authentication, password login, Microsoft Intune® client, IEEE 802.3at Type 2

PoE+ compliant

Wi-Fi® Dual-band 802.11a/b/g/n/ac (2.4 GHz and

5 GHz)

Touch Screen

Display Type TFT active matrix color LCD

Size 7 in. (178 mm) diagonal

Touch Screen Capacitive, multi-touch capable

Resolution 1200 x 800 pixels Crestron Home™ OS UI

Buttons and Indicators

Mic Mute (4) Capacitive buttons with bi-color LEDs, Symbol

toggles between mute and unmute; Green indicates unmute, red indicates mute

Bi-color LED responds to mute and unmute; **Light Bar**

Green indicates unmute, red indicates mute

Audio

Acoustic Automatic gain control, dynamic noise Echo reduction, acoustic echo cancellation, Cancellation

full-duplex IEEE 1329 Type 1 compliant

Speaker Full range speaker;

Amplifier Power: 7 W (rated power); Output Volume: 83 ±3 dBA @1m 1 kHz; Frequency Response: 100 Hz - 20 kHz

Microphones (4) Built-in omnidirectional, digital MEMS

> microphones with 360° audio pickup; Maximum pickup range: 10 ft (3 m) typical

Occupancy Sensor

Detection Approx. 10 ft (3 m) PIR range in front of touch

Range

±45° horizontally Coverage

Pattern

Connectors

LAN (1) 8-pin RJ-45 connector, female;

100BASE-TX/1000BASE-T Ethernet port;

PoE+ PD (powered device) port; PoE+ injector and cables included

USB (1) Micro-USB Type B connector, female;

USB 2.0 device port;

5.8 ft (1.8 m) USB micro-B to A cable included

Kensington Security Slot™ port Security Port

Power

Power over IEEE 802.3af Class 3 and 802.3at Class 4

Ethernet PoE+ powered device;

PoE+ injector included

Dimensions

Height 3.02 in. (77 mm) Width 7.17 in. (182 mm) Depth 9.61 in. (244 mm)

Weight

2.1 lb (0.96 kg)

Compliance

Regulatory Model: M201928001

FCC Part 15 Class B, IC, CE, UL® Listed

Available Accessories

UCA-SMK-UC2

Swivel Mount Kit for Crestron Flex Tabletop Conference

Systems

Tabletop Conference Device for Crestron Home™ OS

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, Crestron Home, and Sonnex are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Kensington Security Slot is either a trademark or registered trademark of ACCO Brands Corporation and its subsidiaries in the United States and/or other countries. Active Directory and Microsoft Intune are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Sonos is either a trademark or registered trademark of Sonos, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. Wi-Fi is either a trademark or registered trademark of Wi-Fi Alliance in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2020 Crestron Electronics, Inc.

Rev 11/19/20



Tabletop Conference Device for Crestron Home™ OS





